

Viva Energy Chemicals

SOLVENT	DENSITY AT 15°C KG/L	BOILING RANGE °C	FLASH POINT °C	SOLUBILITY PARAMETER	RELATIVE EVAP RATE	ANILINE POINT °C	COMPOSITION % M/M		
							P	N	A
Hexane	0.676	62-68	-30	7.3	8.40	65	73	27	0
VivaSol X55	0.697	62-110	-30	7.3	6.80	59	63	37	0
VivaSol X95	0.756	103-135	-1	7.7	2.18	46	41	43	16
VivaSol X3B	0.800	103-135	-1	8.6	2.10	40(M)	22	29	50
White Spirit	0.785	150-191	38	7.9	0.16	50	55	25	20
Mineral Turpentine	0.810	150-190	40	8.4	0.16	23	38	17	45
VivaSol 2046	0.813	201-237	78	7.7	0.01	62	69	14	17
VivaSol 1495	0.795	154-240	41	7.9	0.10	53	53	29	18
VivaSol D80	0.820	201-233	77	7.6	0.01	67	26	74	0
Toluene	0.869	110-111	4	8.9	2.00	9(M)	<2	<1	98
Xylene	0.868	138-141	27	8.9	0.76	11(M)	<1	<1	99
VivaSol A100	0.876	157-171	45	8.8	0.20	14(M)	<2	<1	98