

Technical Datasheet

Product Name

White Spirit 200001730

Product Code

CAS Registry Number

Description

64742-82-1

White Spirit is a narrow boiling range, medium evaporating

solvent widely used in the paint, ink and dry cleaning

industries. White Spirit conforms to Australian Standard AS

3530.

Sales Specification

| Property | Method | Unit | Minimum | Maximum |
|--|------------|------------------------------------|---------|---------|
| Appearance | Visual | Clear & Free From Suspended Matter | | |
| Colour, Saybolt | ASTM D6045 | - | 26 | |
| Density at 15°C | ASTM D4052 | kg/L | 0.775 | 0.790 |
| Distillation, IBP | ASTM D86 | °C | 145 | 155 |
| Distillation, 10% v/v | ASTM D86 | °C | 150 | 160 |
| Distillation, 50% v/v | ASTM D86 | °C | 160 | 170 |
| Distillation, 95% v/v | ASTM D86 | °C | 180 | 190 |
| Distillation, FBP | ASTM D86 | °C | | 200 |
| Flash Point, Abel | IP 170 | °C | 31 | |
| Aniline Point | ASTM D611 | °C | 48 | 56 |
| Aniline Point (85-95% volume fraction) | ASTM D611 | °C | | 65 |
| Copper corrosion | ASTM D130 | - | | 1 |
| Evaporation residue | ASTM D1353 | mg/100mL | | 20 |
| Electrical Conductivity | ASTM D2624 | pS/m | 200 | |

Storage and Handling

Provided proper storage and handling precautions are taken we would expect White Spirit to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet at www.vivaenergy.com.au/services/sds.

Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet at www.vivaenergy.com.au/services/sds.

Typical Properties

| Property | Method | Unit | Value |
|--|------------|-------|-------|
| Colour, Saybolt | ASTM D6045 | - | +30 |
| Density at 15°C | ASTM D4052 | kg/L | 0.785 |
| Distillation, IBP | ASTM D86 | °C | 150 |
| Distillation, 10% v/v | ASTM D86 | °C | 156 |
| Distillation, 50% v/v | ASTM D86 | °C | 165 |
| Distillation, 95% v/v | ASTM D86 | °C | 185 |
| Distillation, FBP | ASTM D86 | °C | 190 |
| Paraffins | GC | % m/m | 55 |
| Naphthenes | GC | % m/m | 25 |
| Aromatics | GC | % m/m | 20 |
| Flash Point, Abel | IP 170 | °C | 38 |
| Aniline Point | ASTM D611 | °C | 52 |
| Aniline Point (85-95% volume fraction) | ASTM D611 | °C | 57 |
| Electrical Conductivity at 23°C | ASTM D2624 | pS/m | 400 |

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM): www.astm.org

Energy Institute (IP): www.energyinst.org.uk

Note: For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained from Viva Energy.

Quality

White Spirit does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Warranty

All products purchased or supplied by Viva Energy are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. Viva Energy warrant that their product will meet those specifications designated as such herein or in other publications. All other information including that herein, supplied by Viva Energy is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the products' suitability for a particular purpose. Viva Energy make no other warranty either expressed or implied, regarding such other information, the data upon which the same is based, or the results to be obtained from use thereof; that any products shall be merchantable or fit for any purpose; or that the use of such other information or product will not infringe any patent.